


Fabas Luce S.p.a. Via Luigi Talamoni 75, 20861 BRUGHERIO MB - ITALY Tel. +39 039 890691 Fax. +39 039 2142208 info@fabasluce.it - www.fabasluce.it


**Olly**LED ceiling lamp particularly slim, with a height of only 50 mm. Aluminum structure. Thanks to its round shape and integrated opal diffuser, this lamp offers uniform, glare-free illumination. Ideal for balconies and terraces. Available in three sizes and two colors.

| Code                          | 3315-65-101                      |
|-------------------------------|----------------------------------|
| Туре                          | Ceiling lamp                     |
| Designer                      | S.T. Fabas Luce                  |
| Eancode                       | 8019282094401                    |
| Customs tariff                | 94051140                         |
| Color                         | Black                            |
| Material                      | Aluminum frame and polycarbonate |
| IP                            | IP54                             |
| IK                            | 10                               |
| Insulation Class              | CL2                              |
| Operating ambient temperature | -10°C + 35°C                     |
| Years of warranty             | 3                                |
| Item Dimensions               | 50mm Ø300mm - 1.2kg              |
| Packaging Dimensions          | 315x315x60mm - 1.4kg             |
|                               | Light Source 1                   |
| Light source                  | LED Included                     |
| LED Characteristics           | SMD                              |
| Light Source Lumen            | 3220 lm                          |
| Item Lumen                    | 2399 lm                          |
| Color Temperature             | Warm white 3000K                 |
| Minimum CRI                   | >80                              |
| Energy Efficiency Class       | ↑ F                              |
|                               | Electrical specifications 1      |
| Input Voltage                 | 220/240V AC 50/60Hz              |
| Total Absorbed Power          | 30W                              |
| Driver                        | Included                         |









 $\epsilon$