



Ravello 595X595

Ravello is a recessed lighting fixture, with a 600x600mm modular structure. It can be installed on the ceiling, suspended and clip-in, with special accessories. Ravello is a LED panel with innovative traits, characterized by great versatility of use, equipped with a backlight optical system that eliminates progressive yellowing of the screen over time. The microprismatic screen guarantees a UGR<19 factor, equipped with LED 3000K or 4000K 42W, CRI >90.

| | |
|--------------------------------------|---|
| Code | 6520-02-003 |
| Type | Recessed lamp |
| Designer | S.T. Fabas Luce |
| Eancode | 8019282558286 |
| Customs tariff | 94054239 |
| Color | White |
| Material | Metal frame / Opal prismatic diffuser |
| IP | IP40 |
| IK | 04 |
| Insulation Class |  CL2 |
| Operating ambient temperature | -20°+50°C |
| Years of warranty | 3 |
| Item Dimensions | 595x595x35mm - 1.7kg |
| Packaging Dimensions | 635x700x40mm - 2.3kg |
| Light Source 1 | |
| Light source | LED Built-in |
| LED Characteristics | SMD |
| Light Source Lumen | 4460 lm |
| Item Lumen | 3620 lm |
| Color Temperature | Warm white 3000K |
| Optics | Prismatic |
| Minimum CRI | >90 |
| Luminous Flux Maintenance | >54.000h L80 B50 |
| UGR | <19 |
| Energy Efficiency Class |  E |
| Electrical specifications 1 | |
| Input Voltage | 220/240V AC 50/60Hz |
| Total Absorbed Power | 42W |
| Driver | Included |
| Power Factor | >0,9 |
| Control System | Dimmable 1-10V |

