



## Ravello 595X595

Ravello is a recessed lighting fixture, with a 600x600mm modular structure. It can be installed on the ceiling, suspended and clip-in, with special accessories. Ravello is a LED panel with innovative traits, characterized by great versatility of use, equipped with a backlight optical system that eliminates progressive yellowing of the screen over time. The microprismatic screen guarantees a UGR<19 factor, equipped with LED 3000K or 4000K 36W, CRI ≥90.

|                                      |                                                                                          |
|--------------------------------------|------------------------------------------------------------------------------------------|
| <b>Code</b>                          | <b>6520-04-005</b>                                                                       |
| <b>Type</b>                          | Recessed lamp                                                                            |
| <b>Designer</b>                      | S.T. Fabas Luce                                                                          |
| <b>Eancode</b>                       | 8019282544616                                                                            |
| <b>Customs tariff</b>                | 94054239                                                                                 |
| <b>Color</b>                         | White                                                                                    |
| <b>Material</b>                      | Metal frame / Opal prismatic diffuser                                                    |
| <b>IP</b>                            | IP40                                                                                     |
| <b>IK</b>                            | 04                                                                                       |
| <b>Insulation Class</b>              | <br>CL2 |
| <b>Operating ambient temperature</b> | -20°+50°C                                                                                |
| <b>Years of warranty</b>             | 3                                                                                        |
| <b>Item Dimensions</b>               | 595x595x35mm                                                                             |
| <b>Light Source 1</b>                |                                                                                          |
| <b>Light source</b>                  | LED Built-in                                                                             |
| <b>LED Characteristics</b>           | SMD                                                                                      |
| <b>Number of LEDs</b>                | 72                                                                                       |
| <b>Light Source Lumen</b>            | 4150 lm                                                                                  |
| <b>Item Lumen</b>                    | 3287 lm                                                                                  |
| <b>Color Temperature</b>             | Natural white 4000 K                                                                     |
| <b>Optics</b>                        | Prismatic                                                                                |
| <b>Typical CRI</b>                   | 90                                                                                       |
| <b>Minimum CRI</b>                   | >90                                                                                      |
| <b>Luminous Flux Maintenance</b>     | >54.000h L80 B50                                                                         |
| <b>UGR</b>                           | <19                                                                                      |
| <b>Energy Efficiency Class</b>       |       |
| <b>Electrical specifications 1</b>   |                                                                                          |
| <b>Input Voltage</b>                 | 220/240V AC 50/60Hz                                                                      |
| <b>Total Absorbed Power</b>          | 36W                                                                                      |
| <b>Driver</b>                        | Included                                                                                 |
| <b>Power Factor</b>                  | >0,9                                                                                     |
| <b>Control System</b>                | On/Off                                                                                   |



CE