

Fabas Luce S.p.a. Via Luigi Talamoni 75, 20861 BRUGHERIO MB - ITALY Tel. +39 039 890691 Fax. +39 039 2142208 info@fabasluce.it - www.fabasluce.it

Ravello 295x1195

Ravello is a recessed lighting fixture, with a 300x1200mm modular structure. Ravello is a LED panel with innovative traits, characterized by great versatility of use, equipped with a backlight optical system that eliminates progressive yellowing of the screen over time. The microprismatic screen guarantees a UGR<19 factor, equipped with LED 3000K or 4000K 36W, CRI ?90.

Code	6520-04-007	
Туре	Recessed lamp	
Designer	S.T. Fabas Luce	
Eancode	8019282559818	-
Customs tariff	94054239	
Color	White	
Material	Metal frame / Opal prismatic diffuser	
IP	IP40	
IK	04	
Insulation Class		
Operating ambient temperature	-20°+50°C	
Years of warranty	3	
Item Dimensions	1195x295x35mm - 1.8kg	
Packaging Dimensions	1300x325x40mm - 2.2kg	
	Light Source 1	
Light source	LED Built-in	
LED Characteristics	SMD	
Number of LEDs	96	
Light Source Lumen	4680 lm	~t
Item Lumen	3536 lm	ř,
Color Temperature	Natural white 4000 K	×
Optics	Prismatic	582
Minimum CRI	>90	1195
Luminous Flux Maintenance	90.000h L80 B50	
UGR	<19	
Energy Efficiency Class		
	Electrical specifications 1	
Input Voltage	220/240V AC 50/60Hz	
Total Absorbed Power	36W	120° Gamma Angles 180° 120°
Driver	Included	100
Power Factor	>0,9	THANKA H
Control System	On/Off	87 87
		14 414 14

CE