

Renoir 28W ON-OFF

Adjustable projector with adapter for installation on mains voltage track for 28W LED source with high yield and monochromatic emission in Warm or Natural White shades, excellent color rendering CRI >90. Integrated electronic ballast in On/Off or DALI versions. The device is made of die-cast aluminum and thermoplastic material, it allows 330° rotation around the vertical axis and an inclination of 90° in relation to the horizontal plane.

Code	6521-94-354
Type	Track spotlight
Designer	S.T. Fabas Luce
Eancode	8019282547280
Customs tariff	94054239
Color	White
Material	Aluminum frame
IP	IP20
IK	04
Insulation Class	 CL2
Operating ambient temperature	-5°C + 35°C
Years of warranty	3
Item Dimensions	100mm Ø85mm - 0,5kg
Packaging Dimensions	210x210x90mm - 0.6kg
Light Source 1	
Light source	LED Built-in
LED Characteristics	COB
Number of LEDs	1
Light Source Lumen	3150 lm
Item Lumen	2919 lm
Color Temperature	Natural white 4000 K
Optics	22°
Minimum CRI	>90
Luminous Flux Maintenance	50.000h L80 B20
Energy Efficiency Class	 E
Electrical specifications 1	
Input Voltage	220/240V AC 50/60Hz
Total Absorbed Power	28W
Driver	Included
Power Factor	>0,9
Control System	On/Off

