

Fabas Luce S.p.a. Via Luigi Talamoni 75, 20861 BRUGHERIO MB - ITALY Tel. +39 039 890691 Fax. +39 039 2142208 info@fabasluce.it - www.fabasluce.it

**Ermes suspension** Suspension LED light which has been designed for use in all ERMES system profiles. This illuminator can be combined with a series of metal diffusers of different shapes and colors or a series of borosilicate glass diffusers of different sizes and finishing in summary, this luminaire combined with the wide range of diffusers represents a versatile and high quality lighting solution, suitable for different environments.

| Code                          | 6525-56-017                   |                            |
|-------------------------------|-------------------------------|----------------------------|
| Туре                          | Suspension lamp               |                            |
| Designer                      | S.T. Fabas Luce               |                            |
| Eancode                       | 8019282557470                 |                            |
| Customs tariff                | 94059900                      |                            |
| Color                         | Black                         |                            |
| Material                      | Aluminum frame                |                            |
| IP                            | IP20                          |                            |
| IK                            | 04                            |                            |
| Insulation Class              | CL3                           |                            |
| Operating ambient temperature | -20°C + 35°C                  |                            |
| Years of warranty             | 3                             | -                          |
| Item Dimensions               | 185xMax 1380mm Ø80mm - 0.18kg |                            |
| Packaging Dimensions          | 200x140x115mm - 0.36kg        |                            |
|                               | Light Source 1                | L 185                      |
| Light source                  | Built-in                      |                            |
| LED Characteristics           | SMD                           |                            |
| Light Source Lumen            | 1510 lm                       |                            |
| Item Lumen                    | 1037 lm                       | H 1350                     |
| Color Temperature             | CCT (2700K 3000K 4000K)       | <u> </u>                   |
| Optics                        | Diffused beam                 |                            |
| Minimum CRI                   | >80                           |                            |
| Energy Efficiency Class       | Ê E                           |                            |
|                               | Electrical specifications 1   | Ø 80                       |
| Input Voltage                 | 48V DC                        | 120° Gamma Anges 130° 120° |
| Total Absorbed Power          | 14W                           |                            |
|                               |                               |                            |
| Control System                | Push dimmer                   |                            |



