

## Peggy 12W

Ceiling recessed LED IP44. Suitable for indoor lighting, offices, reception and open space areas. Metal and polycarbonate frame, color white.

|                                      |                                                                                       |
|--------------------------------------|---------------------------------------------------------------------------------------|
| <b>Code</b>                          | <b>6805-04-157</b>                                                                    |
| <b>Type</b>                          | Recessed lamp                                                                         |
| <b>Designer</b>                      | S.T. Fabas Luce                                                                       |
| <b>Eancode</b>                       | 8019282103936                                                                         |
| <b>Customs tariff</b>                | 94054239                                                                              |
| <b>Color</b>                         | White                                                                                 |
| <b>Material</b>                      | Aluminum frame and polycarbonate                                                      |
| <b>IP</b>                            | IP44                                                                                  |
| <b>IK</b>                            | 04                                                                                    |
| <b>Insulation Class</b>              |  CL2 |
| <b>Hole dimension</b>                |  125 |
| <b>Operating ambient temperature</b> | -20°C +50°C                                                                           |
| <b>Years of warranty</b>             | 5                                                                                     |
| <b>Item Dimensions</b>               | 48mm Ø142mm - 0,30kg                                                                  |
| <b>Packaging Dimensions</b>          | 175x160x80mm - 0.5kg                                                                  |
| <b>Light Source 1</b>                |                                                                                       |
| <b>Light source</b>                  | LED Built-in                                                                          |
| <b>LED Characteristics</b>           | SMD                                                                                   |
| <b>Number of LEDs</b>                | 30                                                                                    |
| <b>Light Source Lumen</b>            | 1850 lm                                                                               |
| <b>Item Lumen</b>                    | 1165 lm                                                                               |
| <b>Color Temperature</b>             | Natural white 4000 K                                                                  |
| <b>Optics</b>                        | Diffused beam                                                                         |
| <b>Typical CRI</b>                   | >80                                                                                   |
| <b>Minimum CRI</b>                   | >80                                                                                   |
| <b>Luminous Flux Maintenance</b>     | > 70.000                                                                              |
| <b>Energy Efficiency Class</b>       |    |
| <b>Electrical specifications 1</b>   |                                                                                       |
| <b>Input Voltage</b>                 | 220/240V AC 50/60Hz                                                                   |
| <b>Total Absorbed Power</b>          | 12W                                                                                   |
| <b>Driver</b>                        | Included                                                                              |
| <b>Power Factor</b>                  | >0,5                                                                                  |
| <b>Control System</b>                | DALI                                                                                  |

