

Turner Suspension lamp

Modular linear profile in extruded aluminum, with opal or microprismatic polycarbonate diffuser UGR<19. Available in 29W/m, warm white or natural white. Integrated power supply for On/Off and DALI; emergency module available on demand. Suitable to be installed as suspension in unidirectional configuration. Complete with suspension and power cable max 2m.

Code	6847-52-101
Type	Light Line Profiles - Suspension lamp
Designer	S.T. Fabas Luce
Eancode	8019282091363
Customs tariff	94054239
Color	White
Material	Aluminum frame
IP	IP40
IK	08
Insulation Class	 CL1
Operating ambient temperature	-20C° +45°
Years of warranty	5
Made In	Italy
Item Dimensions	77x95xMax 2000mm - 3,950/mtkg
Light Source 1	
Light source	LED Built-in
LED Characteristics	SMD
Number of LEDs	70 LED/mt
Light Source Lumen	3470 lm/m
Item Lumen	1951 lm/m
Color Temperature	Warm white 3000K
Optics	Opal
Typical CRI	85
Minimum CRI	80
Luminous Flux Maintenance	>100.000 h L70 B50
Energy Efficiency Class	 E
Electrical specifications 1	
Input Voltage	220/240V AC 50/60Hz
Total Absorbed Power	29W/ml
Driver	Included
Control System	On/Off
Power Supply Type	Costant Current
Driver Output	24V DC
Driver Input	220 - 240 VAC 50/60 Hz

