

Turner Recessed frameless

Modular linear profile in extruded aluminum, with opal or microprismatic polycarbonate diffuser UGR<19. Available in 29W/m , warm white or natural white. Integrated power supply for On/Off and DALI; emergency module available on demand. Suitable to be installed recessed frameless (drywall or masonry)

Code	6849-24-202	
Type	Light Line Profiles – Recessed frameless	
Designer	S.T. Fabas Luce	
Eancode	8019282091578	
Customs tariff	94054239	
Color	Aluminum	
Material	Aluminum frame	
IP	IP40	
IK	08	
Insulation Class	 CL1	
Hole dimension	 82 x L+18	
Operating ambient temperature	-20C° +45°	
Years of warranty	5	
Made In	Italy	
Item Dimensions	77x146mm - 3,950/mtkg	
	Light Source 1	
Light source	LED Built-in	
LED Characteristics	SMD	
Number of LEDs	70 LED/mt	
Light Source Lumen	3570 lm/m	
Item Lumen	2308 lm/m	
Color Temperature	Natural white 4000 K	
Optics	Prismatic	
Typical CRI	85	
Minimum CRI	80	
Luminous Flux Maintenance	>100.000 h L70 B50	
UGR	<19	
Energy Efficiency Class	 E	
	Electrical specifications 1	
Input Voltage	220/240V AC 50/60Hz	
Total Absorbed Power	29W/ml	
Driver	Included	
Control System	On/Off	
Power Supply Type	Costant Current	
Driver Output	24V DC	
Driver Input	220 - 240 VAC 50/60 Hz	

