

## Turner Recessed frameless

Modular linear profile in extruded aluminum, with opal or microprismatic polycarbonate diffuser UGR<19. Available in 29W/m , warm white or natural white. Integrated power supply for On/Off and DALI; emergency module available on demand. Suitable to be installed recessed frameless (drywall or masonry)

|                                    |                                                                                             |
|------------------------------------|---------------------------------------------------------------------------------------------|
| Code                               | 6849-52-202                                                                                 |
| Type                               | Light Line Profiles – Recessed frameless                                                    |
| Designer                           | S.T. Fabas Luce                                                                             |
| Eancode                            | 8019282091523                                                                               |
| Customs tariff                     | 94054239                                                                                    |
| Color                              | White                                                                                       |
| Material                           | Aluminum frame                                                                              |
| IP                                 | IP40                                                                                        |
| IK                                 | 08                                                                                          |
| Insulation Class                   |  CL1       |
| Hole dimension                     |  82 x L+18 |
| Operating ambient temperature      | -20C° +45°                                                                                  |
| Years of warranty                  | 5                                                                                           |
| Made In                            | Italy                                                                                       |
| Item Dimensions                    | 77x146mm - 3,950/mtkg                                                                       |
| <b>Light Source 1</b>              |                                                                                             |
| Light source                       | LED Built-in                                                                                |
| LED Characteristics                | SMD                                                                                         |
| Number of LEDs                     | 70 LED/mt                                                                                   |
| Light Source Lumen                 | 3470 lm/m                                                                                   |
| Item Lumen                         | 2146 lm/m                                                                                   |
| Color Temperature                  | Warm white 3000K                                                                            |
| Optics                             | Prismatic                                                                                   |
| Typical CRI                        | 85                                                                                          |
| Minimum CRI                        | 80                                                                                          |
| Luminous Flux Maintenance          | >100.000 h L70 B50                                                                          |
| UGR                                | <19                                                                                         |
| Energy Efficiency Class            |  E       |
| <b>Electrical specifications 1</b> |                                                                                             |
| Input Voltage                      | 220/240V AC 50/60Hz                                                                         |
| Total Absorbed Power               | 29W/ml                                                                                      |
| Driver                             | Included                                                                                    |
| Control System                     | On/Off                                                                                      |
| Power Supply Type                  | Costant Current                                                                             |
| Driver Output                      | 24V DC                                                                                      |
| Driver Input                       | 220 - 240 VAC 50/60 Hz                                                                      |

