Fabas Luce S.p.a.
Via Luigi Talamoni 75,
20861 BRUGHERIO MB - ITALY
Tel. +39 039 890691
Fax. +39 039 2142208
info@fabasluce.it - www.fabasluce.it

Turner Suspension double emission

Modular linear profile in extruded aluminum, with opal or microprismatic polycarbonate diffuser UGR<19. Available in 29W+15W/m. warm white or natural. Integrated power supply for On/Off and DALI; emergency module available on demand. Suitable to be installed as suspension in the bidirectional configuration. Complete with suspension and power cable max 2m.

Code	**6853-52-222**
Type	Light Line Profiles - Suspension double emission
Designer	S.T. Fabas Luce
Eancode	8019282107804
Customs tariff	94054239
Color	White
Material	Aluminum frame
IP	IP40
IK	08
Insulation Class	CL1
Operating ambient temperature	-20C° +45°
Years of warranty	5
Made In	Italy
Item Dimensions	77x95xMax 2000mm - 3,950/mtkg



	Light Source 1	**Light Source 2**
Light source	LED Built-in	LED Built-in
LED Characteristics	SMD	SMD
Number of LEDs	70 LED/m	140 LED/mt
Light Source Lumen	3470 lm/m	1290 lm/m
Item Lumen	2146 lm/m	1131 lm/m
Color Temperature	Warm white 3000K	Warm white 3000K
Optics	Prismatic	Opal
Typical CRI	85	
Minimum CRI	80	80
Luminous Flux Maintenance	>100.000 h L70 B50	>80.000 h L70 B50
UGR	<19	
Energy Efficiency Class	A↑G E	A↑G E



	Electrical specifications 1	**Electrical specifications 2**
Input Voltage	220/240V AC 50/60Hz	220/240V AC 50/60Hz
Total Absorbed Power	29W/ml	15W/ml
Driver	Included	Included
Control System	DALI	DALI
Power Supply Type	Costant Current	Costant Current
Driver Output	24V DC	24V DC
Driver Input	220 - 240 VAC 50/60 Hz	220 - 240 VAC 50/60 Hz

CE