

## Zeus 135W

High efficiency floodlight for functional and architectural lighting. Suitable especially for outdoor areas. It has a wide range of optics to meet all design needs. Device made of die-cast aluminum copper free EN AB 44100. Polyester painting QUALICOAT (Class 1), corrosion resistant to salt spray for 28 days, conforms to Standard IEC60092-306. Available in grey color RAL 7040, INOX brackets.

|                                    |                                                                                       |
|------------------------------------|---------------------------------------------------------------------------------------|
| Code                               | 6870-04-024                                                                           |
| Type                               | Outdoor Projector                                                                     |
| Designer                           | S.T. Fabas Luce                                                                       |
| Eancode                            | 8019282106142                                                                         |
| Customs tariff                     | 94054239                                                                              |
| Color                              | Grey RAL 7040                                                                         |
| Material                           | Aluminum frame                                                                        |
| IP                                 | IP65                                                                                  |
| IK                                 | 07                                                                                    |
| Insulation Class                   |  CL1 |
| Operating ambient temperature      | -20+35°C                                                                              |
| Years of warranty                  | 5                                                                                     |
| Made In                            | Italy                                                                                 |
| Item Dimensions                    | 384x123x319mm - 6.9kg                                                                 |
| Packaging Dimensions               | 420x170x420mm - 7.3kg                                                                 |
| <b>Light Source 1</b>              |                                                                                       |
| Light source                       | LED Built-in                                                                          |
| LED Characteristics                | SMD                                                                                   |
| Light Source Lumen                 | 18800 lm                                                                              |
| Item Lumen                         | 17320 lm                                                                              |
| Color Temperature                  | Natural white 4000 K                                                                  |
| Optics                             | Asymmetric                                                                            |
| Minimum CRI                        | >80                                                                                   |
| Luminous Flux Maintenance          | >60.000h L70 B50                                                                      |
| Energy Efficiency Class            |    |
| <b>Electrical specifications 1</b> |                                                                                       |
| Input Voltage                      | 220/240V AC 50/60Hz                                                                   |
| Total Absorbed Power               | 132W                                                                                  |
| Driver                             | Included                                                                              |
| Power Factor                       | >0,9                                                                                  |
| Control System                     | On/Off                                                                                |

