

Nizza

High efficiency floodlight for functional and architectural lighting. Suitable especially for outdoor areas. It has a wide range of optics to meet all design needs. Device made of die-cast aluminum copper free EN AB 44100. Polyester painting QUALICOAT (Class 1), corrosion resistant to salt spray for 28 days, conforms to Standard IEC60092-306. Available in grey color RAL 7040, INOX brackets.

Code	6876-04-324
Type	Outdoor Projector
Designer	S.T. Fabas Luce
Eancode	8019282103004
Customs tariff	94054239
Color	Shiny anodized aluminum
Material	Aluminum frame
IP	IP66
IK	08
Insulation Class	 CL1
Operating ambient temperature	-25°C +50°C
Years of warranty	5
Made In	Italy
Item Dimensions	400x100x170,50mm - 2.6kg
Packaging Dimensions	485x125x190mm - 2.9kg
Light Source 1	
Light source	LED Built-in
LED Characteristics	Power LED
Light Source Lumen	6700 lm
Item Lumen	4380 lm
Color Temperature	Natural white 4000 K
Optics	21°
Minimum CRI	>80
Luminous Flux Maintenance	60.000h L70 B50
Energy Efficiency Class	 E
Electrical specifications 1	
Input Voltage	100/240V AC 50/60Hz
Total Absorbed Power	54W
Driver	Included
Power Factor	>0,9
Control System	On/Off

