

Naire 2

Recessed drive-over ground spotlight. Excellent for creating luminous paths. The light, in addition to aiding orientation, creates an evocative path. Resistant to a static load of up to 1700 kg. Application with outer casing supplied. Aluminum structure. Upper front part in AISI 316 stainless steel. Transparent tempered glass diffuser.

Code	6904-02-314	
Type	ground recessed	
Designer	S.T. Fabas Luce	
Eancode	8019282007616	
Customs tariff	94054239	
Color	Stainless steel	
Material	Stainless steel AISI 316L	
IP	IP67	
IK	08	
Insulation Class	 CL1	
Hole dimension	 85	
Operating ambient temperature	-20°C +35°C	
Years of warranty	3	
Item Dimensions	55x55x83mm - 0,40kg	
Packaging Dimensions	95x95x150mm - 0.5kg	
	Light Source 1	
Light source	LED Built-in	
LED Characteristics	SMD	
Light Source Lumen	175 lm	
Item Lumen	152 lm	
Color Temperature	Warm white 3000K	
Optics	30°	
Typical CRI	82	
Energy Efficiency Class	 G	
	Electrical specifications 1	
Input Voltage	220/240V AC 50/60Hz	
Total Absorbed Power	3W	
Driver	Included	

