

## Willy 2

Recessed drive-over ground spotlight. Excellent for creating luminous paths. The light, in addition to aiding orientation, creates an evocative path. Resistant to a static load of up to 780 kg. Application with outer casing, supplied. Aluminum structure. Upper front part in AISI 316 stainless steel. Transparent tempered glass diffuser.

|                                      |   |
|--------------------------------------|---|
| <b>Code</b>                          | <b>6905-02-414</b>  |
| <b>Type</b>                          | ground recessed   |
| <b>Designer</b>                      | S.T. Fabas Luce   |
| <b>Eancode</b>                       | 8019282008767   |
| <b>Customs tariff</b>                | 94054239  |
| <b>Color</b>                         | Stainless steel   |
| <b>Material</b>                      | Stainless steel AISI 316L   |
| <b>IP</b>                            | IP67  |
| <b>IK</b>                            | 08  |
| <b>Insulation Class</b>              |  CL1 |
| <b>Hole dimension</b>                |  95  |
| <b>Operating ambient temperature</b> | -20°C +35°C   |
| <b>Years of warranty</b>             | 3   |
| <b>Item Dimensions</b>               | 96mm Ø70mm - 0.5kg  |
| <b>Packaging Dimensions</b>          | 95x95x145mm - 0.65kg  |
|                                      | <b>Light Source 1</b>   |
| <b>Light source</b>                  | LED Built-in  |
| <b>LED Characteristics</b>           | COB   |
| <b>Light Source Lumen</b>            | 480 lm  |
| <b>Item Lumen</b>                    | 409 lm  |
| <b>Color Temperature</b>             | Warm white 3000K  |
| <b>Optics</b>                        | 32°   |
| <b>Minimum CRI</b>                   | >80   |
| <b>Energy Efficiency Class</b>       |  F |
|                                      | <b>Electrical specifications 1</b>  |
| <b>Input Voltage</b>                 | 220/240V AC 50/60Hz   |
| <b>Total Absorbed Power</b>          | 6,5W  |
| <b>Driver</b>                        | Included  |
| <b>Control System</b>                | On/Off  |

