Fabas Luce S.p.a.
Via Luigi Talamoni 75,
20861 BRUGHERIO MB - ITALY
Tel. +39 039 890691
Fax. +39 039 2142208
info@fabasluce.it - www.fabasluce.it

Irving 2

Recessed drive-over ground spotlight. Excellent for creating luminous paths. The light, in addition to faiding orientation, creates an evocative path. Resistant to a static load of up to 2500 kg. Application with outer casing supplied. Aluminum structure. Upper front part in AISI 316 stainless steel. Transparent tempered glass diffuser.

Code	**6907-02-414**
Type	ground recessed
Designer	S.T. Fabas Luce
Eancode	8019282008781
Customs tariff	94054239
Color	Stainless steel
Material	Stainless steel AISI 316L
IP	IP67
IK	08
Insulation Class	CL1
Hole dimension	102
Operating ambient temperature	-20°C +35°C
Years of warranty	3
Item Dimensions	80mm Ø116mm - 0,80kg
Packaging Dimensions	125x125x170mm - 1kg
	Light Source 1
Light source	LED Built-in
LED Characteristics	COB
Light Source Lumen	750 lm
Item Lumen	653 lm
Color Temperature	Warm white 3000K
Optics	40°
Minimum CRI	>80
Energy Efficiency Class	A G F
	Electrical specifications 1
Input Voltage	220/240V AC 50/60Hz
Total Absorbed Power	7,8W
Driver	Included
Control System	On/Off