

## Egeo 160W

High efficiency floodlight for functional and architectural lighting. Suitable especially for outdoor areas. It has a wide range of optics to meet all design needs. Device made of die-cast aluminum copper free EN AB 44100. Polyester painting QUALICOAT (Class 1), corrosion resistant to salt spray for 28 days, conforms to Standard IEC60092-306. Available in grey color RAL 7040, INOX brackets.

|                                      |                                                                                       |
|--------------------------------------|---------------------------------------------------------------------------------------|
| <b>Code</b>                          | <b>6916-04-324</b>                                                                    |
| <b>Type</b>                          | Outdoor Projector                                                                     |
| <b>Designer</b>                      | S.T. Fabas Luce                                                                       |
| <b>Eancode</b>                       | 8019282106111                                                                         |
| <b>Customs tariff</b>                | 94054239                                                                              |
| <b>Color</b>                         | Grey RAL 7040                                                                         |
| <b>Material</b>                      | Aluminum frame                                                                        |
| <b>IP</b>                            | IP65                                                                                  |
| <b>IK</b>                            | 07                                                                                    |
| <b>Insulation Class</b>              |  CL1 |
| <b>Operating ambient temperature</b> | -20°C +50°C                                                                           |
| <b>Years of warranty</b>             | 5                                                                                     |
| <b>Made In</b>                       | Italy                                                                                 |
| <b>Item Dimensions</b>               | 384x123x319mm - 6.9kg                                                                 |
| <b>Packaging Dimensions</b>          | 420x420x170mm - 7.3kg                                                                 |
| <b>Light Source 1</b>                |                                                                                       |
| <b>Light source</b>                  | LED Built-in                                                                          |
| <b>LED Characteristics</b>           | Power LED                                                                             |
| <b>Light Source Lumen</b>            | 18200 lm                                                                              |
| <b>Item Lumen</b>                    | 16150 lm                                                                              |
| <b>Color Temperature</b>             | Natural white 4000 K                                                                  |
| <b>Optics</b>                        | 63°                                                                                   |
| <b>Minimum CRI</b>                   | >80                                                                                   |
| <b>Luminous Flux Maintenance</b>     | 60.000h L70 B50                                                                       |
| <b>Energy Efficiency Class</b>       |  E |
| <b>Electrical specifications 1</b>   |                                                                                       |
| <b>Input Voltage</b>                 | 220/240V AC 50/60Hz                                                                   |
| <b>Total Absorbed Power</b>          | 160W                                                                                  |
| <b>Driver</b>                        | Included                                                                              |
| <b>Power Factor</b>                  | >0,9                                                                                  |
| <b>Control System</b>                | On/Off                                                                                |

