

 
 Fabas Luce S.p.a.

 Via Luigi Talamoni 75, 20861 BRUGHERIO MB - ITALY

 Tel. +39 039 890691

 Fax. +39 039 2142208

 info@fabasluce.it - www.fabasluce.it

## **Toodle Symmetrical recessed round**

Small round recessed downlight in die-cast aluminum, designed to house COB 11W LEDs with high color rendering CRI> 90. 30° symmetrical emission, supplied as standard with an opal diffuser for diffused emission as optional included. Ideal for residential lighting, waiting and transit areas. Available in White, Gold and Black finishes. Standard supplied with TRIAC power supply (DALI and Emergency kit on demand).

TypeRecessed lampDesignerS.T. Fabas LuceEancode8019282509578Customs tariff94059900ColorWhiteMaterialAluminum frameIPIP40IK06Insulation ClassI0272Operating ambient temperature-20°C +45°CYears of warranty3Item Dimensions89mm Ø82mm - 0,32kgPackaging Dimensions145x125x145mm - 0.45kg
Eancode8019282509578Customs tariff94059900ColorWhiteMaterialAluminum frameIPIP40IK06Insulation ClassI ct2Hole dimension?2°C +45°CYears of warranty3Item Dimensions89mm Ø82mm - 0,32kgPackaging Dimensions145x125x145mm - 0.45kg
Customs tariff94059900ColorWhiteMaterialAluminum frameIPIP40IK06Insulation ClassIIctzHole dimensionIVerating ambient temperature-20°C +45°CYears of warranty3Item Dimensions89mm Ø82mm - 0,32kgPackaging Dimensions145x125x145mm - 0.45kg
ColorWhiteMaterialAluminum frameIPIP40IK06Insulation ClassImportCL2CL2Hole dimensionImportCoperating ambient temperature-20°C +45°CYears of warranty3Item Dimensions89mm Ø82mm - 0.32kgPackaging Dimensions145x125x145mm - 0.45kg
Material       Aluminum frame         IP       IP40         IK       06         Insulation Class       Image: Comparent of the system of
IP       IP40         IK       06         Insulation Class       Image: Class clas cla
IK 06   Insulation Class Image: Class
Insulation Class       Image: Class clas cla
Line       Line         Hole dimension       Image: T2         Operating ambient temperature       -20°C +45°C         Years of warranty       3         Item Dimensions       89mm Ø82mm - 0,32kg         Packaging Dimensions       145x125x145mm - 0.45kg
Operating ambient temperature       -20°C +45°C         Years of warranty       3         Item Dimensions       89mm Ø82mm - 0,32kg         Packaging Dimensions       145x125x145mm - 0.45kg
Years of warranty     3       Item Dimensions     89mm Ø82mm - 0,32kg       Packaging Dimensions     145x125x145mm - 0.45kg
Item Dimensions89mm Ø82mm - 0,32kgPackaging Dimensions145x125x145mm - 0.45kg
Packaging Dimensions     145x125x145mm - 0.45kg
Light Source 1
Light Source 1
Light source LED Built-in
LED Characteristics COB
Light Source Lumen 1220 lm
Item Lumen 1020 Im ♀ ♀ ♀ ♀ ♀ ♀ ♀ ♀ ♀ ♀ ♀ ♀ ♀ ♀ ♀ ♀ ♀ ♀
Color Temperature Warm White 2700K
Optics Symmetric Ø82
Typical CRI 92
Energy Efficiency Class
Electrical specifications 1
Input Voltage 220/240V AC 50/60Hz
Total Absorbed Power 11W
Driver Included
Power Factor >0,9
Control System Triac dimmable

(E 🔾