




Toodle Asymmetrical round recessed

Small round recessed downlight in die-cast aluminum, designed to house COB 11W LEDs with high color rendering CRI> 90. Asymmetrical emission, supplied as standard with an opal diffuser for diffused emission. Ideal for residential lighting, waiting and transit areas. Available in White, Gold and Black finishes. Standard supplied with TRIAC power supply (DALI and Emergency kit on demand).

Code	6960-04-350
Type	Recessed lamp
Designer	S.T. Fabas Luce
Eancode	8019282509806
Customs tariff	94059900
Color	White
Material	Aluminum frame
IP	IP40
IK	06
Insulation Class	 CL2
Hole dimension	 72
Operating ambient temperature	-20°C +45°C
Years of warranty	3
Item Dimensions	89mm Ø82mm - 0,30kg
Packaging Dimensions	145x125x145mm - 0.45kg
Light Source 1	
Light source	LED Built-in
LED Characteristics	COB
Light Source Lumen	1270 lm
Item Lumen	1070 lm
Color Temperature	Natural white 4000 K
Optics	Asymmetric
Typical CRI	92
Energy Efficiency Class	 E
Electrical specifications 1	
Input Voltage	220/240V AC 50/60Hz
Total Absorbed Power	11W
Driver	Included
Power Factor	>0,9
Control System	Triac dimmable

