

## Kris

Small square recessed downlight with asymmetrical emission. Die-cast aluminum body in version with frame and timeless, high color rendering LED CRI> 90. Ideal for residential lighting, waiting and transit areas. Available in Black and White finishes. Supplied as standard with TRIAC power supply (DALI and Emergency kit on demand).

|                                      |                                                                                           |
|--------------------------------------|-------------------------------------------------------------------------------------------|
| <b>Code</b>                          | <b>6961-02-452</b>                                                                        |
| <b>Type</b>                          | Recessed lamp                                                                             |
| <b>Designer</b>                      | S.T. Fabas Luce                                                                           |
| <b>Eancode</b>                       | 8019282509974                                                                             |
| <b>Customs tariff</b>                | 94059900                                                                                  |
| <b>Color</b>                         | White                                                                                     |
| <b>Material</b>                      | Aluminum frame                                                                            |
| <b>IP</b>                            | IP40                                                                                      |
| <b>IK</b>                            | 05                                                                                        |
| <b>Insulation Class</b>              |  CL2     |
| <b>Hole dimension</b>                |  105x105 |
| <b>Operating ambient temperature</b> | -20°C +45°C                                                                               |
| <b>Years of warranty</b>             | 3                                                                                         |
| <b>Item Dimensions</b>               | 93 (150)x93 (150)x58mm - 0.45kg                                                           |
| <b>Packaging Dimensions</b>          | 160x160x110mm - 0.6kg                                                                     |
| <b>Light Source 1</b>                |                                                                                           |
| <b>Light source</b>                  | LED Built-in                                                                              |
| <b>LED Characteristics</b>           | SMD                                                                                       |
| <b>Light Source Lumen</b>            | 930 lm                                                                                    |
| <b>Item Lumen</b>                    | 687 lm                                                                                    |
| <b>Color Temperature</b>             | Warm white 3000K                                                                          |
| <b>Optics</b>                        | Asymmetric                                                                                |
| <b>Typical CRI</b>                   | 90                                                                                        |
| <b>Energy Efficiency Class</b>       |  D     |
| <b>Electrical specifications 1</b>   |                                                                                           |
| <b>Input Voltage</b>                 | 220/240V AC 50/60Hz                                                                       |
| <b>Total Absorbed Power</b>          | 8W                                                                                        |
| <b>Driver</b>                        | Included                                                                                  |
| <b>Power Factor</b>                  | >0,4                                                                                      |
| <b>Control System</b>                | Triac dimmable                                                                            |

