

Millet Recessed frameless

Extruded aluminum profile with cuts every 10 cm., with opal or prismatic polycarbonate diffuser UGR<19. Available in Warm 169lm/W or Natural white 180lm/W temperatures with mid power led 23/Wm. Integrated power supply for On/Off and DALI power supplies, emergency module available on demand.

Code	6971-62-121	
Type	Light Line Profiles – Recessed frameless	
Designer	S.T. Fabas Luce	
Eancode	8019282520412	
Customs tariff	94054239	
Color	Black	
Material	Aluminum frame and polycarbonate	
IP	IP40	
IK	08	
Insulation Class	 CL1	
Hole dimension	 52 X L + 20	
Operating ambient temperature	-25C° +45C°	
Years of warranty	5	
Item Dimensions	46x122mm - 2,2/mkg	
	Light Source 1	
Light source	LED Built-in	
LED Characteristics	SMD	
Number of LEDs	80 LED/mt	
Light Source Lumen	3380 lm/m	
Item Lumen	2124 lm/m	
Color Temperature	Warm white 3000K	
Optics	Opal	
Typical CRI	85	
Minimum CRI	80	
Luminous Flux Maintenance	>100.000 h L80 B10	
Energy Efficiency Class		
	Electrical specifications 1	
Input Voltage	220/240V AC 50/60Hz	
Total Absorbed Power	23W/ml	
Driver	Included	
Control System	DALI	
Power Supply Type	Costant Current	
Driver Output	350mA	
Driver Input	220 - 240 VAC 50/60 Hz	

