

## Millet Recessed frameless

Extruded aluminum profile with cuts every 10 cm., with opal or prismatic polycarbonate diffuser UGR<19. Available in Warm 169lm/W or Natural white 180lm/W temperatures with mid power led 23/Wm. Integrated power supply for On/Off and DALI power supplies, emergency module available on demand.

|                                    |                                                                                               |
|------------------------------------|-----------------------------------------------------------------------------------------------|
| Code                               | 6971-62-202                                                                                   |
| Type                               | Light Line Profiles – Recessed frameless                                                      |
| Designer                           | S.T. Fabas Luce                                                                               |
| Eancode                            | 8019282520375                                                                                 |
| Customs tariff                     | 94054239                                                                                      |
| Color                              | Black                                                                                         |
| Material                           | Aluminum frame and polycarbonate                                                              |
| IP                                 | IP40                                                                                          |
| IK                                 | 08                                                                                            |
| Insulation Class                   |  CL1         |
| Hole dimension                     |  52 X L + 20 |
| Operating ambient temperature      | -25C° +45C°                                                                                   |
| Years of warranty                  | 5                                                                                             |
| Item Dimensions                    | 46x122mm - 2,2/mkg                                                                            |
| <b>Light Source 1</b>              |                                                                                               |
| Light source                       | LED Built-in                                                                                  |
| LED Characteristics                | SMD                                                                                           |
| Number of LEDs                     | 80 LED/mt                                                                                     |
| Light Source Lumen                 | 3380 lm/m                                                                                     |
| Item Lumen                         | 2196 lm/m                                                                                     |
| Color Temperature                  | Warm white 3000K                                                                              |
| Optics                             | Prismatic                                                                                     |
| Typical CRI                        | 85                                                                                            |
| Minimum CRI                        | 80                                                                                            |
| Luminous Flux Maintenance          | >100.000 h L80 B10                                                                            |
| UGR                                | <19                                                                                           |
| Energy Efficiency Class            |            |
| <b>Electrical specifications 1</b> |                                                                                               |
| Input Voltage                      | 220/240V AC 50/60Hz                                                                           |
| Total Absorbed Power               | 23W/ml                                                                                        |
| Driver                             | Included                                                                                      |
| Control System                     | On/Off                                                                                        |
| Power Supply Type                  | Costant Current                                                                               |
| Driver Output                      | 350mA                                                                                         |
| Driver Input                       | 220 - 240 VAC 50/60 Hz                                                                        |

