


Fabas Luce S.p.a.
Via Luigi Talamoni 75,
20861 BRUGHERIO MB - ITALY
Tel. +39 039 890691
Fax. +39 039 2142208
info@fabasluce.it - www.fabasluce.it


RUBENS 16W ON-OFF

Adjustable floodlight with adapter for installation on a track, mains voltage for 16W LED source with high efficiency available in Warm or Natural White shades. Excellent color rendering with COB REAL COLOR CRI 97. Built-in electronic ballast in On/Off or DALI versions. The luminaire is made of diecast aluminum and thermoplastic material, it allows a rotation of 350° around the vertical axis and an inclination of 90° with respect to the horizontal plane. Available in white or black in 15°, 28°, 41° optics.

| Code | 6973-94-354 |
|-------------------------------|-----------------------------|
| Туре | Track spotlight |
| Designer | S.T. Fabas Luce |
| Eancode | 8019282527183 |
| Customs tariff | 94054239 |
| Color | White |
| Material | Aluminum frame |
| IP | IP20 |
| IK | 04 |
| Insulation Class | CL2 |
| Operating ambient temperature | -20°C + 35°C |
| Years of warranty | 5 |
| Made In | Italy |
| Item Dimensions | 95mm Ø55mm - 0.38kg |
| Packaging Dimensions | 200x165x70mm - 0.52kg |
| | Light Source 1 |
| Light source | LED Built-in |
| LED Characteristics | COB |
| Light Source Lumen | 1312 lm |
| Item Lumen | 1134 lm |
| Color Temperature | Natural white 4000 K |
| Optics | 28° |
| Typical CRI | 97 |
| Minimum CRI | 90 |
| Luminous Flux Maintenance | 50.000h L80 B10 |
| Energy Efficiency Class | |
| | Electrical specifications 1 |
| Input Voltage | 220/240V AC 50/60Hz |
| Total Absorbed Power | 16W |
| Driver | Included |
| Power Factor | >0,9 |
| Control System | On/Off |







 ϵ