


Fabas Luce S.p.a.
Via Luigi Talamoni 75,
20861 BRUGHERIO MB - ITALY
Tel. +39 039 890691
Fax. +39 039 2142208
info@fabasluce.it - www.fabasluce.it


## **RUBENS 28W BASKET**

Adjustable recessed LED projector for basket, gimbal, made of die-cast aluminium, with a compact light design and a rotation on both axis vertical and horizontal. COB REAL COLOR CRI 97 guarantees an excellent color rendering and a particular brilliancy. The reflectors grant high system efficiency and they are available in different beam angles. Available in 28W and 36W Cob Led, On/Off. RUBENS is a versatile product suitable for all types of installation, from commercial to cultural areas.

| Code                          | 6974-72-254                 |
|-------------------------------|-----------------------------|
| Туре                          | Basket recessed             |
| Designer                      | S.T. Fabas Luce             |
| Eancode                       | 8019282529651               |
| Customs tariff                | 94054239                    |
| Color                         | White                       |
| Material                      | Aluminum frame              |
| IP                            | IP40                        |
| IK                            | 03                          |
| Insulation Class              | CL2                         |
| Operating ambient temperature | -20°C +35°C                 |
| Years of warranty             | 5                           |
| Item Dimensions               | 129mm Ø111mm - 1.3kg        |
| Packaging Dimensions          | 210x190x210mm - 1.6kg       |
|                               | Light Source 1              |
| Light source                  | LED Built-in                |
| LED Characteristics           | COB                         |
| Light Source Lumen            | 2600 lm                     |
| Item Lumen                    | 1970 lm                     |
| Color Temperature             | Warm white 3000K            |
| Optics                        | 20°                         |
| Typical CRI                   | 97                          |
| Minimum CRI                   | 90                          |
| Luminous Flux Maintenance     | 50.000h L80 B10             |
| Energy Efficiency Class       | Î E                         |
|                               | Electrical specifications 1 |
| Input Voltage                 | 220/240V AC 50/60Hz         |
| Total Absorbed Power          | 28W                         |
| Driver                        | Included                    |
| Power Factor                  | >0,9                        |
| Control System                | On/Off                      |







 $\epsilon$