

 Fabas Luce S.p.a.

 Via Luigi Talamoni 75,

 20861 BRUGHERIO MB - ITALY

 Tel. +39 039 890691

 Fax. +39 039 2142208

 info@fabasluce.it - www.fabasluce.it

## **RUBENS 36W RECESSED**

Adjustable recessed LED projector made of die-cast aluminium, with a compact light design and a rotation on both axis vertical and horizontal. COB REAL COLOR CRI 97 guarantees an excellent color rendering and a particular brilliancy. The reflectors grant high system efficiency and they are available in different beam angles. Available in 28W and 36W Cob Led, On/Off. Emergency kit on demand. RUBENS is a versatile product suitable for all types of installation, from commercial to cultural areas.

| Code                          | 6975-64-554                 |                             |
|-------------------------------|-----------------------------|-----------------------------|
| Туре                          | Recessed lamp               |                             |
| Designer                      | S.T. Fabas Luce             |                             |
| Eancode                       | 8019282529590               |                             |
| Customs tariff                | 94054239                    | Millionia.                  |
| Color                         | White                       |                             |
| Material                      | Aluminum frame              | 0                           |
| IP                            | IP40                        |                             |
| IK                            | 03                          |                             |
| Insulation Class              |                             |                             |
| Hole dimension                | 175                         |                             |
| Operating ambient temperature | -20°C +35°C                 |                             |
| Years of warranty             | 5                           |                             |
| Item Dimensions               | 140mm Ø200mm - 1.4kg        |                             |
| Packaging Dimensions          | 210x190x210mm - 1.7kg       |                             |
|                               | Light Source 1              |                             |
| Light source                  | LED Built-in                |                             |
| LED Characteristics           | СОВ                         |                             |
| Light Source Lumen            | 4000 lm                     |                             |
| Item Lumen                    | 3105 lm                     | Ø 200                       |
| Color Temperature             | Natural white 4000 K        |                             |
| Optics                        | 45°                         |                             |
| Typical CRI                   | 97                          |                             |
| Luminous Flux Maintenance     | 50.000h L80 B10             | 120° Gamma Angles 580° 120° |
| Energy Efficiency Class       |                             |                             |
|                               | Electrical specifications 1 |                             |
| Input Voltage                 | 220/240V AC 50/60Hz         |                             |
| Total Absorbed Power          | 36W                         | 19 <b>19</b>                |
| Driver                        | Included                    | - or                        |
| Power Factor                  | >0,9                        |                             |
| Control System                | On/Off                      |                             |