



Manet 600x600 IP55

Direct emission ceiling lamp IP55 for recessed installation or ceiling-mounted with special accessory. Optical compartment in painted metal, UGR<19 microprismatic shield, Mid power LED 40W high yield CRI 90. White finish, Warm and Natural White. Electronic power supply On/Off, dimmable DALI or 0-10V included. Emergency kit on demand. IP55 version is perfect for lighting offices, open spaces and for general lighting in large areas.

Code	6982-04-015
Type	Recessed lamp
Designer	S.T. Fabas Luce
Eancode	8019282525486
Customs tariff	94054239
Color	White
Material	Metal frame / Clear prismatic diffuser
IP	IP55
IK	05
Insulation Class	 CL2
Operating ambient temperature	-20°C +45°C
Years of warranty	5
Item Dimensions	595x595x61mm - 3.0kg
Packaging Dimensions	610x660x90mm - 3.7kg
Light Source 1	
Light source	LED Built-in
LED Characteristics	SMD
Light Source Lumen	5500 lm
Item Lumen	4347 lm
Color Temperature	Natural white 4000 K
Optics	Prismatic
Minimum CRI	>90
Luminous Flux Maintenance	>54.000 L70 B50
UGR	<19
Energy Efficiency Class	 D
Electrical specifications 1	
Input Voltage	220/240V AC 50/60Hz
Total Absorbed Power	40W
Driver	Included
Power Factor	> 0.9
Control System	On/Off

