


Fabas Luce S.p.a. Via Luigi Talamoni 75, 20861 BRUGHERIO MB - ITALY Tel. +39 039 890691 Fax. +39 039 2142208 info@fabasluce.it - www.fabasluce.it

Manet 300x1200 Clip in

Direct emission ceiling lamp for recessed stand-in. Optical compartment in painted metal, UGR<19 microprismatic shield, Mid power LED 40W high yield CRI 90. White finish, Warm and Natural White. Electonic power supply On/Off, dimmable DALI o 0-10V included. Emergency kit on demand. Perfect for lighting offices, open spaces and for general lighting in large areas.

| Code | 6988-02-715 | |
|-------------------------------|--|---|
| Туре | Recessed lamp | |
| Designer | S.T. Fabas Luce | and the second se |
| Eancode | 8019282530572 | |
| Customs tariff | 94054239 | |
| Color | White | |
| Material | Metal frame / Clear prismatic diffuser | |
| IP | IP40 | |
| IK | 05 | |
| Insulation Class | | |
| Operating ambient temperature | -20°C +45°C | |
| Years of warranty | 5 | |
| Item Dimensions | 300x1200x62mm - 3,20kg | |
| Packaging Dimensions | 1122x370x90mm - 4.2kg | |
| | Light Source 1 | |
| Light source | Built-in | |
| LED Characteristics | SMD | 300 |
| Number of LEDs | 210 | |
| Light Source Lumen | 5100 lm | |
| Color Temperature | Warm white 3000K | 1200 |
| Optics | Prismatic | 1 EUU |
| Typical CRI | > 90 | |
| Luminous Flux Maintenance | >54.000h L70 B50 | |
| UGR | <19 | |
| Energy Efficiency Class | | 139° Gamma Angles 180° 139° |
| | Electrical specifications 1 | |
| Input Voltage | 220/240V AC 50/60Hz | 87 19 67 00 |
| Total Absorbed Power | 40W | |
| Driver | Included | |
| Power Factor | > 0.9 | |
| Control System | On/Off | |



CE